

DIGITAL PRESSURE GAUGE MGA N32-2

PRECISE & RELIABLE

MGA N32-2

INTRODUCING OUR STATE-OF-THE-ART DIGITAL PRESSURE GAUGE, ENGINEERED FOR UNPARALLELED PRECISION WITH AN ACCURACY OF 0.05% FULL SCALE (FS). DESIGNED FOR RELIABILITY AND CONSISTENCY, THIS GAUGE ENSURES ACCURATE PRESSURE READINGS, MAKING IT THE PERFECT TOOL FOR PROFESSIONALS WHO REQUIRE THE HIGHEST STANDARDS IN MEASUREMENT PERFORMANCE. THIS GAUGE IS AVAILABLE IN PRESSURE RANGES UPTO 3000 BAR.



ZERO

-1:7 bar

UNITS

ESC

CAL

MAX

KEY FEATURES:

- USER-FRIENDLY INTERFACE: EASY TO OPERATE, ENSURING SMOOTH AND EFFICIENT USE.
- VERSATILE DISPLAY: SHOWS READINGS IN 10 DIFFERENT PRESSURE UNITS FOR MAXIMUM CONVENIENCE.



- ROBUST ENGINEERING: BUILT TO BE DURABLE AND LONG-LASTING, EVEN IN HARSH CONDITIONS.
- CUSTOMIZABLE: TAILORED TO THE SPECIFIC RANGE REQUIREMENTS SPECIFIED BY THE USER.
- WIDE RANGE: AVAILABLE IN PRESSURE RANGES FROM -1 TO 3000 BAR.
- ABSOLUTE RANGE OPTION: ABSOLUTE PRESSURE RANGE IS ALSO AVAILABLE FOR SPECIALIZED APPLICATIONS.
- NABL CERTIFIED: SUPPLIED WITH A NABL CERTIFIED CALIBRATION REPORT.*

SPECIFICATIONS

Accuracy	0.05% Full Scale (FS) upto 1000 bar	
Display	128x64 Backlit Graphic Display (Battery % and Min&Max displayed)	
Pressure Units	kg/cm2, bar, psi, Pa, kPa, mmHg, mmWc/mmH20, inHg, inWc/inH2O, mbar	
Pressure Media	Depends on Sensor used SS304 for 2 bar and above Dry Air only for low pressure applications	
Overrange Protection	125% of specified range	
Process Connection	1/4 " BSP	
Enclosure	Plastic Body, ABS Dye Moulded. 90 mm diameter	
Power	Battery Operated (5 x AAA batteries, Sony LR03 or equivalent)	

Battery Life	Approx. 90 hours
Low Battery	Battery life displayed in percentage

CONTACT US FOR FURTHER DETAILS

>

+91-9316743396 +91-9825161223



spatil@vijayenterprises.in | contact@vijayenterprises.in



A-202 Arihant Supermarket, Opp SBI Lalbaug, Manjalpur, Vadodara, Gujarat 390011